

# Material Safety Data Sheet (MSDS)

Product	1.0% Sulfur B-C		
CAS No.	Issuing date	Last revised date	Department
64741-45-3	2008-07-25	2018-05-18	Safety / Health Planning Team

#### 1. IDENTIFICATION

#### A. Product name

- 1.0% Sulfur B-C

#### B. Recommended use and restriction on use

- General use : Fuel

- Restriction on use : Not available

# 3) Manufacturer/Supplier/Distributor Information

- Supply Company: GS Caltex Corporation

- Address: GS Tower, 508, Nonhyeon-ro, Gangnam-gu, Seoul, Korea

Information service or emergency call: (02) 1544-5151Department in charge: The customer service center

#### 2. HAZARD IDENTIFICATION

#### A. GHS Classification

Flammable liquids: Category4
Skin corrosion/irritation: Category2
Carcinogenicity: Category1B
Acute aquatic toxicity: Category3
Chronic aquatic toxicity: Category3

# B. GHS label elements

## ○ Hazard symbols





# ○ Signal words

- Danger

#### O Hazard statements

- H227 Combustible liquid
- H315 Causes skin irritation
- H350 May cause cancer
- H402 Harmful to aquatic organisms.
- H412 Harmful to aquatic life with long lasting effects

# $\bigcirc$ Precautionary statements

#### 1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P264 Wash hands thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### 2) Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.

- P308+P313 If exposed or concerned: Get medical advice/attention.
- P321 Specific treatment
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

#### 3) Storage

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

#### 4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

## C. Other hazards which do not result in classification: (NFPA Classification)

#### ○ NFPA grade (0 ~ 4 level)

- Health: 2, Flammability: 2, Reactivity: 0

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
ATMOSPHERICTOWER RESIDUE (REDUCED CRUDE	-	64741-45-3	99
Sulfur, precipitated, sublimed or colloidal	Colloidal sulfur ; Brimstone	7704-34-9	<1

#### 4. FIRST AID MEASURES

#### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

#### **B. Skin contact**

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contaminated clothing, shoes and isolate.
- Wash thoroughly after handling.
- Wear gloves when washing the patient, and please avoid contact with contaminated clothing.

#### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

#### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.

# E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

#### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

## 5. FIREFIGHTING MEASURES

#### A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

#### B. Specific hazards arising from the chemical

- Not available

#### C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Keep unauthorized personnel out.
- Do not access if the tank on fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.

#### 6. ACCIDENTAL RELEASE MEASURES

## A. Personal precautions, protective equipment and emergency procedures

- Must work against the wind, let the upwind people to evacuate.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Handling the damaged containers or spilled material after wearing protective equipment.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

#### **B.** Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

# C. Methods and materials for containment and cleaning up

- Large spill: Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces.
- Spilled material should be treated as a potential risk of waste collected.

#### 7. HANDLING AND STORAGE

#### A. Precautions for safe handling

- Comply with all applicable laws and regulations for handling
- Get the manual before use.
- Refer to Engineering controls and personal protective equipment.
- Do not handle until all safety precautions have been read and understood.
- Do not inhale the steam prolonged or repeated.
- Contaminated work clothing should not be allowed out of the workplace.

## B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Check regularly for leaks.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Keep sealed when not in use.

- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### A. Exposure limits

- **ACGIH TLV** 
  - Not available
- O OSHA PEL
  - Not available

# **B.** Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

## C. Individual protection measures, such as personal protective equipment

#### O Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

#### ○ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

#### O Hand protection

- Wear appropriate chemical resistant glove.

### $\bigcirc$ Skin protection

- Wear appropriate chemical resistant protective clothing.

#### ○ Others

- Not available

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid(Viscous liquid)
- Color	Dark Brown
B. Odor	Strong Hydrocarbon
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	Not available
F. Initial Boiling Point/Boiling Ranges	> 230 ℃
G. Flash point	> 70 ℃
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	5.0%/1.0%
K. Vapour pressure	Not available
L. Solubility	Not available
M. Vapour density	Not available

N. Specific gravity(Relative density)	<0.991
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	Not available
Q. Decomposition temperature	Not available
R. Viscosity	< 380mm²/s @ 50°C
S. Molecular weight	Not available

#### 10. STABILITY AND REACTIVITY

#### A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

## B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

#### C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

## D. Incompatible materials

- Not available

#### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

# 11. TOXICOLOGICAL INFORMATION

## A. Information on the likely routes of exposure

- (Respiratory tracts)
  - Not available
- (Oral)
  - Not available
- (Eye·Skin)
  - Causes skin irritation

## B. Delayed and immediate effects and also chronic effects from short and long term exposure

- O Acute toxicity
  - \* Oral
    - Product (ATEmix): >5000mg/kg
    - [Fuel oil, residual] : LD50 > 2000 mg/kg Rat
    - [Sulfur, precipitated, sublimed or colloidal] : LD50 > 5000 mg/kg Rat
  - \* Dermal
    - Product (ATEmix) : >5000mg/kg
    - [Fuel oil, residual] : LD50 > 2000 mg/kg Rat
    - [Sulfur, precipitated, sublimed or colloidal] : LD50 > 2000 mg/kg Rabbit
  - \* Inhalation
    - Product (ATEmix) : Not available [Fuel oil, residual] : No data
- Skin corrosion/irritation
  - Causes skin irritation
- $\bigcirc$  Serious eye damage/irritation
  - Not available
- O Respiratory sensitization
  - Not available
- O Skin sensitization
  - Not available
- Carcinogenicity
  - \* IARC

- [Fuel oil, residual] : Group 2B
- \* OSHA
  - Not available
- \* ACGIH
  - Not available
- \* NTP
  - Not available
- \* EU CLP
  - [Fuel oil, residual] : Carc. 1B
- Germ cell mutagenicity
  - Not available
- O Reproductive toxicity
  - Not available
- STOT-single exposure
  - Not available
- STOT-repeated exposure
  - Not available
- O Aspiration hazard
  - Not available

## 12. ECOLOGICAL INFORMATION

## A. Ecotoxicity

- Fish
  - [Fuel oil, residual] : LC50 35 mg/ℓ 96 hr Pimephales promelas (IUCLID)
  - [Sulfur, precipitated, sublimed or colloidal] : LC50 866 mg/ $\ell$  96 hr Brachydanio rerio (UBA, IUCLID)
- Crustaceans
  - [Sulfur, precipitated, sublimed or colloidal] : EC50 ≥ 5000 mg/ℓ 48 hr Daphnia magna (ECOTOX)
- Algae
  - [Fuel oil, residual] : EC50 160 mg/ $\ell$  96 hr Skeletonema costatum (IUCLID)

## B. Persistence and degradability

- **Persistence** 
  - [Fuel oil, residual] : log Kow 2.7 ~ 6 (IUCLID)
  - [Sulfur, precipitated, sublimed or colloidal] : log Kow = 0.23
- $\bigcirc$  Degradability
  - Not available

# C. Bioaccumulative potential

- O Bioaccumulative potential
  - Not available
- O Biodegration
  - [Fuel oil, residual]: 11 (%) 28 day (Aerobic, Industrial wastewater contaminated with oil, very slowly decomposes) (IUCLID)

#### D. Mobility in soil

- Not available

## E. Other adverse effects

- Not available

# 13. DISPOSAL CONSIDERATIONS

## A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Incinerate the oil by separating the oil and water

- The remainder of the water after separation will be processed in a water pollution prevention facilities.
- Do incineration or stabilization of the residue after disposal as the method of evaporation and concentration.
- Do incineration of the residue after disposal as the method of agglomeration and precipitation.
- Take care of incinerate or stabilization after treatment, purified by means of Separation distillation extractio filtration pyrolysis

#### B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

#### 14. TRANSPORT INFORMATION

#### A. UN No. (IMDG CODE/IATA DGR)

- 1993

#### B. Proper shipping name

- Fuel Oil

#### C. Hazard Class

- 3

### D. IMDG CODE/IATA DGR Packing group

- Ⅲ

#### E. Marine pollutant

- Not applicable

#### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

# 15. REGULATORY INFORMATION

## A. National and/or international regulatory information

- O POPs Management Law
  - Not applicable
- O Information of EU Classification
  - \* Classification
    - [Fuel oil, residual] : H350
    - [Sulfur, precipitated, sublimed or colloidal] : H315
- U.S. Federal regulations
  - \* OSHA PROCESS SAFETY (29CFR1910.119)
    - Not applicable
  - \* CERCLA Section 103 (40CFR302.4)
    - Not applicable
  - \* EPCRA Section 302 (40CFR355.30)
    - Not applicable
  - \* EPCRA Section 304 (40CFR355.40)
    - Not applicable
  - \* EPCRA Section 313 (40CFR372.65)
    - Not applicable
- O Rotterdam Convention listed ingredients
  - Not applicable
- $\bigcirc$  Stockholm Convention listed ingredients
  - Not applicable

## O Montreal Protocol listed ingredients

- Not applicable

## 16. OTHER INFORMATION

## A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

#### B. Issue date

- 2008-07-25

## C. Revision number and Last date revised

- 2 times, 2018-05-18

## D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).