



# Material Safety Data Sheet (MSDS)

<b>Product</b>	<b>Kerosene</b>		
<b>CAS No.</b>	<b>Date of preparation</b>	<b>Date of preparation</b>	<b>Department of Team</b>
8008-20-6	2008-07-25	2019-02-20	Safety / Health Planning Team

## 1. IDENTIFICATION

### A. Product name

- Kerosene [PD1093]

### B. Recommended use and restriction on use

- General use : Fuel  
- Restriction on use : Not available

### C. Manufacturer / Supplier / Distributor information

#### ○ Manufacturer information

- Company name : GS Caltex Corporation  
- Address : 508 Nonhyun-ro, Gangnam-gu, Seoul, Korea

#### ○ Supplier/Distributor information

- Company name : GS Caltex Corporation  
- Address : 508 Nonhyun-ro, Gangnam-gu, Seoul, Korea  
- Telephone number : 82-1544-5151  
- Emergency telephone number : 82-1544-5151  
- Fax number : 02-565-5168

## 2. HAZARD IDENTIFICATION

### A. GHS Classification

- Flammable liquids : Category3  
- Skin corrosion/irritation : Category2  
- Carcinogenicity : Category2  
- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)  
- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)  
- Aspiration hazard : Category1  
- Acute aquatic toxicity : Category2  
- Chronic aquatic toxicity : Category2

### B. GHS label elements

#### ○ Hazard symbols



#### ○ Signal words

- Danger

#### ○ Hazard statements

- H226 Flammable liquid and vapour  
- H304 May be fatal if swallowed and enters airways  
- H315 Causes skin irritation  
- H335 May cause respiratory irritation.  
- H336 May cause drowsiness and dizziness.  
- H351 Suspected of causing cancer

- H401 Toxic to aquatic organisms.
- H411 Toxic to aquatic life with long lasting effects

#### ○ Precautionary statements

##### 1) Prevention

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

##### 2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).
- P391 Collect spillage.

##### 3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

##### 4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

#### C. Other hazards which do not result in classification : (NFPA Classification)

##### ○ NFPA grade (0 ~ 4 level)

- Health : 2 , Flammability : 2, Reactivity : 0

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Kerosine	-	8008-20-6	100

### 4. FIRST AID MEASURES

#### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.
- Get medical attention immediately.

#### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Wash thoroughly after handling.

### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.
- If breathing is stopped or irregular, give artificial respiration and supply oxygen.

### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

### E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.
- If exposed or concerned, get medical attention/advice.

## 5. FIREFIGHTING MEASURES

### A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

### B. Specific hazards arising from the chemical

- Not available

### C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk.
- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Due to the extremely low flash point, irrigating fire extinguishing may be less effective when put out a fire.

## 6. ACCIDENTAL RELEASE MEASURES

### A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Must work against the wind, let the upwind people to evacuate.
- Move container to safe area from the leak area.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Avoid skin contact and inhalation.
- Cleanup and disposal under expert supervision is advised.
- Keep unauthorized people away, isolate hazard area and deny entry.

### B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

### C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Do not use plastic containers.
- Prevent the influx to waterways, sewers, basements or confined spaces.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Get the manual before use.
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.
- Avoid contact with heat, sparks, flame or other ignition sources.
- Contaminated work clothing should not be allowed out of the workplace.

### B. Conditions for safe storage, including any incompatibilities

- Save in cool, dry and well ventilated place.
- Do not apply any physical shock to container.
- Avoid direct sunlight.
- Keep sealed when not in use.
- No open fire.
- By specifying a storage area for carcinogenic substances.
- Collected them in sealed containers.
- Store away from water and sewer.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

- ACGIH TLV**
  - [Kerosine] : TWA, 200 mg/m<sup>3</sup>, Total hydrocarbon vapor Skin
- OSHA PEL**
  - Not available

### B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

### C. Individual protection measures, such as personal protective equipment

- Respiratory protection**
  - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
  - Respiratory protection is ranked in order from minimum to maximum.
  - Consider warning properties before use.
- Eye protection**
  - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
  - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- Hand protection**
  - Wear appropriate chemical resistant glove.
- Skin protection**
  - Wear appropriate chemical resistant protective clothing.
- Others**
  - Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
---------------	--

- Appearance	Liquid
- Color	Transparent
B. Odor	Fuel Smell
C. Odor threshold	Not available
D. pH	Not available
E. Melting point/Freezing point	-20°C
F. Initial Boiling Point/Boiling Ranges	140 °C ~ 270 °C
G. Flash point	≥38 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	LEL: 0.7%, UEL: 5.0%
K. Vapour pressure	5mmHg @ 38°C
L. Solubility	Insoluble
M. Vapour density	4.5
N. Specific gravity(Relative density)	0.78 ~ 0.82
O. Partition coefficient of n-octanol/water	Not available
P. Autoignition temperature	220°C
Q. Decomposition temperature	Not available
R. Viscosity	> 1.3 cSt @ 40°C
S. Molecular weight	Not available

## 10. STABILITY AND REACTIVITY

### A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

### B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

### C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

### D. Incompatible materials

- Not available

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

- (Respiratory tracts)
  - May be fatal if swallowed and enters airways
  - May cause respiratory irritation.
- (Oral)
  - Not available
- (Eye-Skin)
  - Causes skin irritation

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
  - \* Oral
    - [Kerosine] : LD50 > 5000 mg/kg Rat (No deaths OECD Guideline 402, GLP)
  - \* Dermal
    - [Kerosine] : LD50 > 2000 mg/kg Rabbit (NLM: ChemIDPlus)
  - \* Inhalation

- [Kerosine] : vapor LC50 >5.28 mg/ℓ 4 hr Rat (no death OECD Guideline 403, GLP)

- Skin corrosion/irritation**
  - Causes skin irritation
- Serious eye damage/irritation**
  - Not available
- Respiratory sensitization**
  - Not available
- Skin sensitization**
  - Not available
- Carcinogenicity**
  - \* **IARC**
    - Not available
  - \* **OSHA**
    - Not available
  - \* **ACGIH**
    - [Kerosine] : A3
  - \* **NTP**
    - Not available
  - \* **EU CLP**
    - Not available
- Germ cell mutagenicity**
  - Not available
- Reproductive toxicity**
  - Not available
- STOT-single exposure**
  - May cause drowsiness and dizziness.
  - May cause respiratory irritation.
- STOT-repeated exposure**
  - Not available
- Aspiration hazard**
  - May be fatal if swallowed and enters airways

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

- Fish**
  - Not available
- Crustaceans**
  - Not available
- Algae**
  - Not available

### B. Persistence and degradability

- Persistence**
  - Not available
- Degradability**
  - Not available

### C. Bioaccumulative potential

- Bioaccumulative potential**
  - Not available
- Biodegradation**
  - [Kerosine] : 58.6 % 28 day (non-biodegradable, (OECD Guideline 301 FP))

### D. Mobility in soil

- [Kerosine] : Koc 50000 ~ 670

### E. Other adverse effects

- Not available

### 13. DISPOSAL CONSIDERATIONS

#### A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.
- Incinerate the oil by separating the oil and water
- The remainder of the water after separation will be processed in a water pollution prevention facilities.
- Do incineration or stabilization of the residue after disposal as the method of evaporation and concentration.
- Do incineration of the residue after disposal as the method of agglomeration and precipitation.
- Take care of incinerate or stabilization after treatment, purified by means of Separation•distillation•extractio•filtration•pyrolysis

#### B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

### 14. TRANSPORT INFORMATION

#### A. UN No. (IMDG CODE/IATA DGR)

- 1223

#### B. Proper shipping name

- KEROSENE

#### C. Hazard Class

- 3

#### D. IMDG CODE/IATA DGR Packing group

- III

#### E. Marine pollutant

- Applicable

#### F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-E (Flammable liquids, floating on water)

### 15. REGULATORY INFORMATION

#### A. National and/or international regulatory information

- POPs Management Law**
  - Not applicable
- Information of EU Classification**
  - \* **Classification**
    - [Kerosine] : H304
- U.S. Federal regulations**
  - \* **OSHA PROCESS SAFETY (29CFR1910.119)**
    - Not applicable
  - \* **CERCLA Section 103 (40CFR302.4)**
    - Not applicable
  - \* **EPCRA Section 302 (40CFR355.30)**
    - Not applicable
  - \* **EPCRA Section 304 (40CFR355.40)**

- Not applicable
- \* **EPCRA Section 313 (40CFR372.65)**
  - Not applicable
- Rotterdam Convention listed ingredients**
  - Not applicable
- Stockholm Convention listed ingredients**
  - Not applicable
- Montreal Protocol listed ingredients**
  - Not applicable

## 16. OTHER INFORMATION

### A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

### B. Issue date

- 2008-07-25

### C. Revision number and Last date revised

- 2 times, 2019-02-07

### D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).

